




ZANA

URBAN AND PARK LIGHTING

VPA10 3030B UG30

VPA10 3030B UG40

VPA10 3030B UG60



MECHANICAL SPECS / MEKANİK ÖZELLİKLER

| | |
|---|---|
| Application Areas Uygulama Alanları | Residential areas - Terminals - Parks and gardens - Parking lots |
| Luminaire Type Ürün Tipi | LED Urban and Park Luminaires |
| Luminaire Body Ürün Gövdesi | Aluminum body. Electrostatic powder coating |
| Luminaire Diffuser Ürün Difüzörü | Lenses |
| Luminaire Colour Ürün Gövde Rengi | S : Ral 9005 Jet black / B : Ral 9016 Traffic White / G : Ral 9006 Grey |
| Ingress Protection (IP) Rating IP Sınıfı | IP66 |
| Impact Resistance (IK) Rating IK Sınıfı | IK08 |

OPTICAL SPECS / OPTİK ÖZELLİKLER

| | |
|--|--------------------------------|
| Light Source Işık Kaynağı | Mid Power LED |
| CRI Value CRI Değeri | >80 |
| UGR Value UGR Değeri | <21 (EN124664-1) |
| Photo Biological Class Fotobiyolojik Risk Grubu | Group-0 No Risk |
| Beam Angle Işık Açısı | 60° |
| Driver (220-240V) Sürücü | Osram - Tridonic & ENEC Driver |

ELECTRICAL SPECS / ELEKTRİKSEL ÖZELLİKLER

| | |
|---|----------------|
| Mains Voltage Giriş Gerilimi | 220-240 V |
| Mains Frequency Frekans | 50/60 Hz |
| Protection Class Koruma Sınıfı | I |
| Led Service (25°C) Led Ömrü | L80 = 50.000 h |
| Power Factor Güç Faktörü | >0,958 |
| Operating Temperature Çalışma Sıcaklığı | -35°C & -55°C |
| Hot Wire Resistance Kablo Sıcaklık Direnci | 650°C |

OPTIONS / OPSİYONLAR

| | | | |
|-----------------------------|-----------------------------|-------------|---------------|
| 1 Hour Emergency Kit | 3 Hour Emergency Kit | DALI | SENSOR |
| + | + | + | - |

| Product Code Ürün Kodu | Power (W) Watt | Lumen (lm) Işık Akısı | Efficacy (lm/W) Verimlilik | Col. Temp (K) Kelvin | Dimensions (mm) Boyutlar (a x b x c) Ø | Pack. Qty Koli Adedi | Pack. Weight (kg) Koli Ağırlığı |
|---------------------------|-------------------|--------------------------|-------------------------------|-------------------------|---|-------------------------|------------------------------------|
| VPA10 3030B UG30 | 30 | 3000 | 100 | 3000 | 150x150x3000 | 1 | 10,00 |
| VPA10 3030B UG40 | 30 | 3000 | 100 | 4000 | 150x150x3000 | 1 | 10,00 |
| VPA10 3030B UG60 | 30 | 3000 | 100 | 6000 | 150x150x3000 | 1 | 10,00 |