



CORA

DOWNLIGHTS AND SPOTLIGHTS

VSP03 8032E AB30
VSP03 8032E AB40
VSP03 8032E AB60

MECHANICAL SPECS / MEKANİK ÖZELLİKLER

Application Areas Uygulama Alanları	Supermarket - Office building - School - Retail area - Residences
Luminaire Type Ürün Tipi	LED Downlights and Spotlights
Luminaire Body Ürün Gövdesi	Die cast aluminum. Electrostatic powder coating
Luminaire Diffuser Ürün Difüzörü	Opal glass with reflector
Luminaire Colour Ürün Gövde Rengi	S : Ral 9005 Jet black / B : Ral 9016 Traffic White / G : Ral 9006 Grey
Ingress Protection (IP) Rating IP Sınıfı	IP40
Impact Resistance (IK) Rating IK Sınıfı	IK03

OPTICAL SPECS / OPTİK ÖZELLİKLER

Light Source Işık Kaynağı	Mid Power COB LED
CRI Value CRI Değeri	>80
UGR Value UGR Değeri	<21 (EN124664-1)
Photo Biological Class Fotobiyolojik Risk Grubu	Group-0 No Risk
Beam Angle Işık Açısı	120°
Driver (220-240V) Sürücü	Osram - Tridonic & ENEC Driver

ELECTRICAL SPECS / ELEKTRİKSEL ÖZELLİKLER

Mains Voltage Giriş Gerilimi	220-240 V
Mains Frequency Frekans	50/60 Hz
Protection Class Koruma Sınıfı	I
Led Service (25°C) Led Ömrü	L80=50.000h
Power Factor Güç Faktörü	>0,957
Operating Temperature Çalışma Sıcaklığı	-20°C & -45°C
Hot Wire Resistance Kablo Sıcaklık Direnci	650°C

OPTIONS / OPSİYONLAR

1 Hour Emergency Kit	3 Hour Emergency Kit	DALI	SENSOR
+	+	+	-

Product Code Ürün Kodu	Power (W) Watt	Lumen (lm) Işık Akısı	Efficacy (lm/W) Verimlilik	Col. Temp (K) Kelvin	Dimensions (mm) Boyutlar (a bxc) Ø	Pack. Qty Koli Adedi	Pack. Weight (kg) Koli Ağırlığı
VSP03 8032E AB30	32	3200	100	3000	240x240x50x210	20	1,00
VSP03 8032E AB40	32	3200	100	4000	240x240x50x210	20	1,00
VSP03 8032E AB60	32	3200	100	6000	240x240x50x210	20	1,00